

LISTING OF THE CLAIMS:

This listing of claims will replace all prior versions and listings of claims in the application:

Claims 1-9. (Cancelled)

Claim 10. (Currently amended) ~~The connecting member as in claim 8~~ A connecting member for releasably connecting a first part to a second part, the connecting member comprising:

a housing having a second opening; and

a second locking member having a second tab and a second button, said second locking member being on said housing such that said second locking member biases said second tab through said second opening, said second tab being releasably connectable to the second part in said housing when said second tab is biased through said second opening, and said second locking member being configured such that pressure on said second button moves said second tab from the second part, wherein said second locking member has a major axis and a minor axis, said second tab being along said minor axis and said second button being along said major axis.

Claim 11. (Currently amended) The connecting member as in claim ~~[[8]]~~ 10, further comprising a first retaining rim on said housing for maintaining said second locking member in a selected position.

Claim 12. (Original) The connecting member as in claim 11, further comprising a second rim on said housing to maintain said second locking member in said selected position between said first and second retaining rims.

Claim 13. (Original) The connecting member as in claim 12, wherein said second retaining rim includes an inwardly depending tab for securing said second retaining rim to a fourth opening in said housing.

Claim 14. (Currently amended) ~~The connecting member as in claim 8, further comprising:~~

A connecting member for releasably connecting a first part to a second part, the connecting member comprising:

a housing having a second opening;

a second locking member having a second tab and a second button, said second locking member being on said housing such that said second locking member biases said second tab through said second opening, said second tab being releasably connectable to the second part in said housing when said second tab is biased through said second opening, and said second locking member being configured such that pressure on said second button moves said second tab from the second part; and

a first locking member having a first tab and a first button, said first locking member being in said housing such that said first locking member biases said first tab through a first opening and said first button through a third opening, said first tab being releasably connectable to the first part when said first locking member biases said first tab through said first opening, and said first button remaining uncovered by the first part when the first part is releasably connected to said first tab.

Claims 15-21. (Cancelled)

Claim 22. (Currently amended) ~~The connecting member as in claim 24~~ A connecting member for connecting a first part to a second part, the connecting member comprising:
a housing having a first end and a second end, said first end being configured for connection to the first part and said second end being configured for connection to the second part;
a pair of retaining rims extending from said housing;
an opening defined in said housing between said pair of retaining rims; and
a locking member having a tab and a button, said locking member disposed about said housing between said pair of retaining rims so that said tab is normally biased through said opening into the second part but so that pressure on said second button removes said second tab from the second part, wherein said ~~second~~ locking member has a major axis and a minor axis, said tab being along said minor axis and said button being along said major axis.